

# Policy Implications of Hybrid Predictive Models for Pipeline Integrity Management: Enhancing Maintenance Decision Support in Nigeria's Oil and Gas Sector

Muhammad Bala Maradun,<sup>1,2</sup> Umar Usman,<sup>1</sup>

<sup>1</sup>Department of Statistics, Usman Danfodiyo University, Sokoto,

<sup>2</sup>University Health Services Department, Federal University, Gusau.

Corresponding Author's Email: [balamaradun@gmail.com](mailto:balamaradun@gmail.com), [mbmaradun@fugusau.edu.ng](mailto:mbmaradun@fugusau.edu.ng)

## ABSTRACT

Nigeria's oil and gas sector depends on an extensive pipeline network that has sustained cumulative economic losses exceeding US \$658.5 million from pipeline failures between 1990 and 2022 (Ekeu-wei and Ekeu-wei, 2024). Predominantly, reactive maintenance regimes have failed to arrest this trend. This paper explores the policy implications and national impact of a hybrid neural–statistical predictive maintenance framework applied to Nigeria's pipeline sector. The framework integrates four deep-learning architectures—Feedforward Artificial Neural Networks (ANN), Long Short-Term Memory (LSTM) networks, Convolutional Neural Networks (CNN), and Graph Neural Networks (GNN)—with Generalised Additive Models (GAM) and Exponentiated–Exponentiated Weibull (EEW) survival distributions to predict Remaining Useful Life (RUL) with calibrated uncertainty bounds. Model evaluation against Nigeria-specific pipeline sensor data demonstrated that the hybrid framework outperformed all benchmarks: it achieved a Root Mean Square Error (RMSE) of 8.3 days, a Mean Absolute Error (MAE) of 6.1 days, and a coefficient of determination ( $R^2$ ) of 0.96, compared with  $R^2$  values of 0.93 (LSTM), 0.91 (ANN), and 0.82 (traditional Weibull). For binary failure classification, the hybrid model attained 95.4% accuracy, 92.1% precision, 96.3% recall, and an F1-score of 94.1%. These results indicate that sector-wide adoption of predictive maintenance could reduce annual operational costs by approximately 35%, cutting average unscheduled downtime from 30 to 12 days per year and halving repair and replacement expenditure. The paper contextualises these findings within Nigeria's regulatory landscape—particularly the Petroleum Industry Act (2021) and the Nigerian Upstream Petroleum Regulatory Commission (NUPRC) regulations—and provides evidence-based policy recommendations for policymakers and industry stakeholders to improve operational safety, reduce costs, and mitigate the environmental impact of pipeline failures.

**Keywords:** Predictive Maintenance; Hybrid Models; Policy Implications; Pipeline Lifespan; Remaining Useful Life; Oil and Gas Sector; Environmental Impact; Nigeria; Regulatory Framework; Maintenance Strategy.

## 1.0 INTRODUCTION

Pipeline infrastructure forms the arterial network of Nigeria's oil and gas sector, conveying crude oil, natural gas, and refined products across the country. Despite its economic centrality, this infrastructure has proven chronically vulnerable to failure. Corrosion, mechanical stress, soil movements, and the progressive deterioration of ageing pipelines have produced a legacy of costly incidents that have undermined production, contaminated ecosystems, and endangered communities. Between 1990 and 2022, cumulative economic losses attributable to pipeline failures exceeded US \$658.5 million (Ekeu-wei and Ekeu-wei, 2024). Oil spills and gas leaks resulting from these failures have caused environmental damage that in many Niger Delta communities remains unresolved decades after the initial incidents.

The dominant maintenance paradigm in the sector has been reactive: inspections and repairs are performed after failure rather than in anticipation of it. This approach produces predictable consequences—high emergency repair costs, unplanned production downtime, regulatory

penalties, and environmental remediation expenditures—all of which are, in principle, avoidable with timely intelligence about impending failures. Predictive maintenance, which employs data-driven models to forecast the RUL of pipeline segments before failure occurs, offers a practicable and economically attractive alternative (Hussain *et al.*, 2023; Shaik *et al.*, 2022).

Recent advances in machine learning and statistical modelling have produced hybrid frameworks that combine the predictive accuracy of deep learning with the interpretability and uncertainty quantification of classical statistical methods. Such frameworks are particularly well-suited to the pipeline integrity domain, where decisions must be defensible to regulators and comprehensible to maintenance engineers. The Petroleum Industry Act of 2021 created two principal regulatory bodies—the NUPRC and the Nigerian Midstream and Downstream Petroleum Regulatory Authority (NMDPRA)—that are positioned to mandate and enforce data-driven maintenance standards (Federal Republic of Nigeria, 2021). This paper introduces a hybrid neural–statistical framework for pipeline RUL



uncertainty quantification in safety-critical applications. Brown and Davis (2024) showed that Bayesian neural networks improved monitoring reliability and produced probabilistic predictions suitable for regulatory communication. Wilson *et al.* (2024) applied conformal prediction to construct distribution-free confidence intervals for hybrid model outputs, demonstrating their legal defensibility for inspection scheduling under regulatory mandates. Amadheet *et al.* (2024) reviewed machine learning applications for pipeline integrity management and concluded that ensemble and meta-learning strategies yield more robust RUL predictions than single-model approaches. Rayhana *et al.* (2024) confirmed these findings in a non-destructive evaluation context, demonstrating that hybrid predictive frameworks consistently outperformed conventional NDE methods for pipeline integrity assessment. Van Dinter *et al.* (2024) identified interpretability, uncertainty quantification, and regulatory alignment as the three critical design requirements for predictive maintenance systems deployed in safety-critical industries.

#### 2.4 Regulatory Context and Policy Developments

Nigeria's regulatory environment for pipeline management has undergone significant reform. The Petroleum Industry Act (Federal Republic of Nigeria, 2021) restructured upstream and midstream oversight, creating the NUPRC and NMDPRA as the principal regulatory authorities for their respective segments of the industry. The NUPRC Gas Flaring, Venting and Methane Emissions Regulations (NUPRC, 2023) introduced mandatory emissions monitoring and established penalties for non-compliance, creating direct financial incentives for operators to prevent pipeline failures that cause fugitive gas emissions. The NUPRC 2024 Annual Report (NUPRC, 2024) documented continued enforcement activity and highlighted the need for operators to adopt advanced monitoring technologies as a condition of licence renewal. Hector and Panjanathan (2024) surveyed planning models and machine learning techniques for predictive maintenance in Industry 4.0 contexts, finding that clear regulatory compliance pathways were the most effective enablers of industry-wide technology adoption. Ezeja and Nwobi (2024) demonstrated the feasibility of wireless sensor networks for pipeline monitoring in Nigeria, confirming that the technical infrastructure required to support predictive maintenance is increasingly available domestically.

#### 2.5 Research Gap

Despite the body of evidence reviewed above, several significant gaps remain. First, most prior studies address either predictive accuracy or model interpretability, but rarely both simultaneously in a single integrated framework. Second, there is limited research on the

application of hybrid neural–statistical models that combine deep learning with survival analysis and conformal prediction specifically for regulatory compliance purposes in the pipeline sector. Third, the existing literature contextualised within Nigeria's specific operational, environmental, and regulatory landscape remains thin relative to the scale of the challenge the country faces. Fourth, performance reporting in existing studies often omits regression-based accuracy measures (RMSE, MAE,  $R^2$ ), limiting engineers' and policymakers' ability to assess model suitability for real-world maintenance scheduling. This paper addresses all four gaps by proposing, validating, and policy-contextualising a hybrid framework that satisfies both the technical and regulatory requirements of Nigeria's pipeline sector, and by reporting a full suite of performance metrics.

#### 3. Materials and Methods

This section presents the mathematical formulation of the hybrid neural–statistical framework for pipeline RUL prediction. The framework integrates four neural network architectures with a Generalised Additive Model (GAM) and an Exponentiated–Exponentiated Weibull (EEW) survival distribution. Input variables include operational sensor data—pipeline pressure, wall-thickness corrosion rate, flow velocity, and operating temperature as well as environmental covariates such as soil conductivity and ambient climatic conditions. All components share a common data pre-processing pipeline applied to Nigeria-specific pipeline sensor data drawn from the Niger Delta operational environment.

##### 3.1 Formal Definition of Remaining Useful Life

Let  $T$  denote the random failure time of a pipeline segment and  $t$  the current inspection time. The Remaining Useful Life at time  $t$  is defined as:

$$RUL(t) = T - t, \text{ given } T > t \quad (1)$$

Because  $T$  is a random variable, all component models estimate the conditional expectation  $E[RUL(t) | X(t)]$ , where  $X(t) = (x_1, x_2, \dots, x_m)$  is the sensor-covariate vector observed at time  $t$ , encompassing pipeline pressure, corrosion rate, soil conductivity, operating temperature, and flow velocity.

##### 3.2 Feedforward Artificial Neural Network (ANN)

A fully connected ANN with  $L$  hidden layers maps the static feature vector  $X(t)$  to a scalar RUL estimate. The forward pass at layer  $l$  is:

$$h^l = \text{sigma}(W^l h^{(l-1)} + b^l), \quad l = 1, \dots, L \quad (2)$$

$$RUL_{ANN}(t) = W^{out} h^L + b^{out} \quad (3)$$

where  $W^l$  and  $b^l$  are learnable weight matrices and bias vectors,  $h^0 = X(t)$ , and  $\text{sigma}(\cdot)$  is the ReLU activation function  $\max(0, z)$ . The network is trained by minimising the mean squared error loss using mini-batch stochastic gradient descent with the Adam optimiser.

##### 3.3 Long Short-Term Memory Network (LSTM)

The LSTM processes the sequential degradation history  $X_{(1:t)} = \{X_{(1)}, X_{(2)}, \dots, X_{(t)}\}$  through gated memory cells. At each time step  $\tau$ , the update equations are:

$$f_{\tau} = \sigma(W^f [h_{(\tau-1)}, X_{(\tau)}] + b^f) \quad [\text{forget gate}] \quad (4)$$

$$i_{\tau} = \sigma(W^i [h_{(\tau-1)}, X_{(\tau)}] + b^i) \quad [\text{input gate}] \quad (5)$$

$$C_{\tau} = \tanh(W^c [h_{(\tau-1)}, X_{(\tau)}] + b^c) \quad [\text{candidate cell}] \quad (6)$$

$$C_{\tau} = f_{\tau} \circ C_{(\tau-1)} + i_{\tau} \circ C_{\tau} \quad [\text{cell state}] \quad (7)$$

$$h_{\tau} = o_{\tau} \circ \tanh(C_{\tau}), \quad o_{\tau} = \sigma(W^o [h_{(\tau-1)}, X_{(\tau)}] + b^o) \quad [\text{output}] \quad (8)$$

The operator  $\circ$  denotes element-wise (Hadamard) multiplication. The final hidden state  $h^T$  is passed through a linear readout layer to yield  $RUL_{LSTM}(t)$ . Gated memory prevents gradient vanishing across long sequences, enabling the LSTM to capture slow corrosion-driven degradation trends spanning months or years—critical for Nigerian pipeline segments exposed to persistent saline soil conditions (Shaik *et al.*, 2022).

### 3.4 Convolutional Neural Network (CNN)

A 1-D CNN extracts local degradation patterns from a sliding window of length  $w$  applied to the multivariate sensor signal. For the  $k$ -th convolutional filter with kernel  $K^k$  and stride  $s$ , the feature map is:

$$Z^k(j) = \sigma(\sum_m K^k(m) \cdot X(js + m) + b^k) \quad (9)$$

Global average pooling is applied across the temporal dimension, and the resulting feature vector is fed to a dense regression head. The CNN excels at detecting short-burst anomalies such as pressure transients and sudden corrosion-pit initiation (Spandonidis *et al.*, 2022).

### 3.5 Graph Neural Network (GNN) for Spatial Dependencies

The pipeline network is modelled as a graph  $G = (V, E, A)$ , where each node  $v_i$  represents a monitored segment, each edge  $e_{ij}$  represents physical connectivity or shared soil conditions, and  $A$  is the weighted adjacency matrix. The graph convolutional message-passing update at layer  $l$  is (Wang *et al.*, 2025):

$$h_i^{(l+1)} = \sigma(W^l \sum_{j \in N(i)} (A_{ij} / \sqrt{d_i d_j}) h_j^{(l)} + b^l) \quad (10)$$

where  $N(i)$  is the neighbourhood of node  $i$ , and  $d_i$  is the degree of node  $i$ . After  $L$  propagation layers, a readout function yields the per-segment  $RUL_{GNN}(t)$ . This architecture captures the propagation of corrosion or pressure anomalies between adjacent segments—particularly significant in Niger Delta pipeline clusters (Amadheet *et al.*, 2024; Wen *et al.*, 2024).

### 3.6 Generalised Additive Model (GAM) Component

The GAM provides an interpretable, statistically grounded baseline prediction. It models the conditional

mean RUL as a sum of smooth univariate functions of each covariate (Wood, 2020):

$$g(E[RUL(t) | X(t)]) = \alpha + \sum_j f_j(x_j) + \epsilon \quad (11)$$

Here  $g(\cdot)$  is a log link function ensuring positive RUL predictions,  $\alpha$  is the global intercept,  $f_j(\cdot)$  is a penalised cubic regression spline for covariate  $x_j$ , and  $\epsilon \sim N(0, \sigma^2)$  is the residual. Each smooth is estimated by maximising a penalised log-likelihood:

$$l_{pen}(f) = l(f) - (1/2) \sum_j \lambda \int [f_j''(x)]^2 dx \quad (12)$$

where  $\lambda_j > 0$  is a smoothing penalty tuned by restricted maximum likelihood (REML). The GAM's additive structure makes the effect of each covariate on RUL directly readable from a partial-effect plot, enabling regulatory auditors to scrutinise model reasoning without requiring machine-learning expertise (Clark *et al.*, 2023; Wood, 2020).

### 3.7 Exponentiated-Exponentiated Weibull (EEW) Survival Distribution

The EEW distribution models the stochastic failure time  $T$  with shape parameters  $\alpha, \beta, \theta > 0$ , and a scale parameter  $\lambda > 0$ . Its cumulative distribution function (CDF) is:

$$F(t; \alpha, \beta, \theta, \lambda) = \{1 - \exp[-(\lambda t)^{\alpha}] \}^{\beta \theta} \quad (13)$$

The survival function  $S(t) = 1 - F(t)$  gives the probability of survival beyond time  $t$ . The hazard function  $h(t) = f(t)/S(t)$  characterises the instantaneous failure rate, and the conditional expected RUL is:

$$E[RUL | T > t] = (1/S(t)) \int_t^{\infty} S(u) du \quad (14)$$

The EEW extends the two-parameter Weibull by adding shape flexibility, enabling bathtub-, unimodal-, or monotone-hazard profiles—all observed in Niger Delta pipeline segments of differing ages and corrosion histories (Kumar *et al.*, 2022). Parameters are estimated via maximum likelihood, and bootstrap confidence intervals provide uncertainty bands for the RUL estimate.

### 3.8 Hybrid Ensemble Integration and Uncertainty Quantification

The five component predictions— $RUL_{ANN}$ ,  $RUL_{LSTM}$ ,  $RUL_{CNN}$ ,  $RUL_{GNN}$ , and  $RUL_{GAM}$ —are combined through a stacked meta-learner. A second-level linear regression is trained on out-of-fold cross-validation predictions from each base model:

$$RUL_{Hybrid}(t) = \beta_1 RUL_{ANN} + \beta_2 RUL_{LSTM} + \beta_3 RUL_{CNN} + \beta_4 RUL_{GNN} + \beta_5 RUL_{GAM} + \beta_0 \quad (15)$$

Predictive uncertainty is quantified using conformal prediction. For a new test point, the non-conformity score is  $\alpha_i = |RUL_i - RUL_{Hybrid}(t_i)|$ . At coverage

probability  $1-\epsilon$  (e.g., 90%), the prediction interval is:

$$C(t) = [RUL_{Hybrid}(t) - q_{\hat{}}(1-\epsilon), RUL_{Hybrid}(t) + q_{\hat{}}(1-\epsilon)] \quad (16)$$

where  $q_{\hat{}}(1-\epsilon)$  is the  $(1-\epsilon)$ -quantile of the calibration non-conformity score distribution, this

distribution-free guarantee ensures that  $C(t)$  contains the true RUL with probability at least  $1-\epsilon$ , regardless of the underlying data distribution, making the interval legally defensible for inspection scheduling under NUPRC mandates (Wilson *et al.*, 2024; Federal Republic of Nigeria, 2021).

Table 1: Summary of Model Components, Equations, and Roles in the Hybrid RUL Framework

Component	Key Equation(s)	Role in Framework	Key Strength
ANN	Eqs. (2)-(3)	Static feature mapping from sensor snapshot to RUL	Fast inference; captures nonlinear covariate interactions
LSTM	Eqs. (4)-(8)	Temporal degradation trend modelling over extended sequences	Handles long-range corrosion sequences without gradient vanishing
CNN	Eq. (9)	Local anomaly and pattern detection within sensor windows	Detects pressure transients and sudden corrosion-pit events
GNN	Eq. (10)	Spatial risk propagation modelling across the pipeline network graph	Captures corrosion propagation between adjacent pipeline segments
GAM	Eqs. (11)-(12)	Interpretable statistical baseline; partial-effect audit trail	Transparent nonlinear covariate effects are readable by regulators
EEW Survival	Eqs. (13)-(14)	Probabilistic failure-time distribution and survival function	Flexible hazard profiles; bootstrap confidence intervals on RUL
Hybrid Ensemble	Eqs. (15)-(16)	Stacked meta-learner with conformal prediction intervals	Distribution-free coverage guarantee is legally defensible for regulators

*Note.* Equation numbers refer to the formulations in Section 3. All neural components share a common Nigeria-specific training pipeline; the GAM and EEW are fitted independently and integrated via the stacked meta-learner in Equation 15. ANN = Artificial Neural Network; LSTM = Long Short-Term Memory; CNN = Convolutional Neural Network; GNN = Graph Neural Network; GAM = Generalised Additive Model; EEW = Exponentiated-Exponentiated Weibull.

Table 1 provides a consolidated overview of the seven model components that constitute the hybrid framework. Reading across the rows, a clear and complementary division of labour is evident: the ANN and CNN are responsible for capturing instantaneous sensor patterns and local temporal anomalies respectively; the LSTM models sustained degradation trends over extended time horizons; the GNN encodes spatial risk propagation across the interconnected pipeline network; the GAM furnishes the interpretable statistical baseline required for

regulatory audit; the EEW distribution models probabilistic failure timing with bootstrap uncertainty bands; and the stacked ensemble integrates all component outputs into a single, uncertainty-bounded RUL estimate ready for operational and regulatory use.

## 4.0 RESULTS

### 4.1 Model Performance Evaluation

The hybrid framework was evaluated against three benchmark models—standalone ANN, LSTM, and the traditional Weibull distribution—using stratified time-series and spatial cross-validation on Nigeria-specific pipeline sensor data. Performance was assessed using both regression metrics (RMSE, MAE,  $R^2$ ) for the continuous RUL prediction task and classification metrics (Accuracy, Precision, Recall, F1-Score) for the binary failure detection task. The comprehensive metric suite presented in Table 5 directly addresses the measurement gaps identified in Section 2.5.

Table 2 Comparative Model Performance: Regression and Classification Metrics Across All Evaluated Models

Model	RMSE (days)	MAE (days)	$R^2$	Accuracy (%)	Precision (%)	Recall (%) / F1 (%)
-------	-------------	------------	-------	--------------	---------------	---------------------

Hybrid Model (EEW + Neural Networks)	8.3	6.1	0.96	95.4	92.1	96.3 / 94.1
ANN (Artificial Neural Network)	14.7	11.2	0.91	91.2	88.7	92.5 / 90.5
LSTM (Long Short-Term Memory)	11.4	8.9	0.93	93.5	90.2	94.7 / 92.4
Traditional Weibull Model	21.6	17.3	0.82	88.4	83.1	85.6 / 84.3


*Note.* RMSE = Root Mean Square Error (days of RUL); MAE = Mean Absolute Error (days of RUL); R<sup>2</sup> = coefficient of determination for the RUL regression task. Accuracy, Precision, Recall, and F1-Score refer to binary failure/no-failure classification. All values are means across five stratified cross-validation folds. Lower RMSE and MAE and higher R<sup>2</sup> indicate stronger regression performance; higher Accuracy, Precision, Recall, and F1-Score indicate stronger classification performance.

As shown in Table 2, the hybrid model (EEW + Neural Networks) achieved the best performance across all reported metrics. For RUL regression, it produced an RMSE of 8.3 days, an MAE of 6.1 days, and an R<sup>2</sup> of 0.96—substantially outperforming the LSTM (R<sup>2</sup> = 0.93, RMSE = 11.4 days), ANN (R<sup>2</sup> = 0.91, RMSE = 14.7 days), and traditional Weibull benchmarks (R<sup>2</sup> = 0.82, RMSE = 21.6 days). The traditional Weibull model's

RMSE of 21.6 days and MAE of 17.3 days confirm the inadequacy of purely parametric approaches for the complex, multi-factor pipeline degradation environment of the Niger Delta. For the failure classification task, the hybrid model attained 95.4% accuracy, 92.1% precision, 96.3% recall, and a 94.1% F1-score—indicating that it reliably identifies impending failure events whilst maintaining a low false-positive rate, a balance essential for cost-efficient maintenance scheduling without excessive unnecessary interventions.

#### 4.2 Risk-Based Maintenance Decision Framework

Figure 1 presents the risk-based maintenance decision framework derived from the hybrid model's RUL predictions. The framework classifies pipeline segments into three risk tiers based on their model-predicted RUL and failure probability, and maps each tier to a corresponding maintenance strategy.




**Figure 1.** Risk-Based Maintenance Decision Framework Derived from Hybrid Model RUL and Failure Probability Outputs  
As illustrated in Figure 1, pipeline segments classified as low risk (high RUL, low failure probability) are assigned to routine monitoring and standard periodic inspection schedules. Moderate-risk segments (moderate RUL, medium failure probability) trigger condition-based maintenance, involving more frequent inspections and targeted preventive interventions. High-risk segments (low RUL, high failure probability) require immediate

predictive maintenance, including corrective actions informed by real-time sensor data. This structured, model-driven framework ensures that inspection and repair resources are directed to where they are most urgently needed, maximising risk reduction per unit of maintenance expenditure and providing a clear, auditable basis for regulatory compliance reporting. The direct correspondence between the framework's three tiers and the inspection frequency recommendations in Table 3

enables regulators to translate model outputs into enforceable maintenance schedules.

#### 4.3 Environmental Impact Reduction

Figure 2 presents projected reductions in environmental incidents achievable through sector-wide implementation of the hybrid predictive maintenance framework, comparing modelled incident rates under reactive and predictive maintenance regimes.




**Figure 2.** Projected Environmental Impact Reduction Through Hybrid Predictive Maintenance Implementation

As shown in Figure 2, adopting the hybrid predictive maintenance framework is projected to reduce oil spill incidents by approximately 40% and gas leak events by 35% relative to the reactive maintenance baseline. These reductions result from the model's ability to identify high-risk pipeline segments before failure, enabling targeted interventions that prevent the most environmentally harmful events. The environmental gains illustrated in Figure 2 carry direct regulatory significance: fewer spill incidents mean fewer triggers for liability under the NUPRC Methane Emissions Regulations (NUPRC, 2023), substantially reduced remediation costs, and a stronger compliance record in

regulatory reviews. These projections are consistent with findings reported by Hussain *et al.* (2023), who documented significant reductions in environmental incident frequency when real-time sensor-driven maintenance was implemented in comparable pipeline-intensive operating environments.

#### 4.4 Resource Allocation Optimisation via RUL Prediction

Figure 3 illustrates how pipeline resource allocation—inspection scheduling, crew deployment, and capital expenditure prioritisation—can be systematically optimised by using RUL predictions generated by the hybrid framework.



**Figure 3.** Optimised Resource Allocation Framework Based on Hybrid Model RUL Predictions

As shown in Figure 3, pipeline segments with model-predicted RUL values below an operational threshold (for example, 30 days) are flagged for immediate inspection and corrective maintenance, whilst segments with longer predicted remaining lives are assigned to scheduled routine monitoring. This differentiated approach eliminates redundant expenditures associated with uniform, fixed-interval inspections of healthy pipeline sections, concentrating resources on segments that genuinely require attention. The resource allocation scheme depicted in Figure 3 provides the operational

mechanism by which the 37% reduction in annual maintenance expenditure reported in Table 4 is achieved, and it directly underpins the maintenance prioritisation and inspection interval recommendations set out in Table 3.

#### 4.5 Comparative Cost Analysis

Table 2 presents a comparative cost analysis contrasting traditional reactive maintenance with the predictive maintenance approach enabled by the hybrid framework, based on sector-level cost data for Nigeria's pipeline industry (Ekeu-wei and Ekeu-wei, 2024).

**Table 3** Comparative Cost Analysis of Reactive Versus Predictive Maintenance Strategies

Maintenance Strategy	Estimated Annual Cost (N)	Key Benefits
Traditional Reactive Maintenance	N1.5 billion	High downtime; emergency repairs; extensive environmental damage and remediation costs
Predictive Maintenance (Hybrid Model)	N800 million	Reduced downtime; proactive scheduled repairs; substantially lower environmental incident and remediation costs

*Note.* Cost figures are indicative annual estimates for a representative Nigerian pipeline operator, derived from sector-level data reported in Ekeu-wei and Ekeu-wei (2024). Benefits are qualitative characterisations supported by the quantitative findings in Tables 4 and 5. N = Nigerian Naira.

As Table 3 shows, replacing traditional reactive maintenance (estimated annual cost: N1.5 billion) with hybrid model-driven predictive maintenance (estimated annual cost: N800 million) yields annual savings of approximately N700 million per operator. These savings are attributable principally to the elimination of large

emergency repair costs, the reduction of unscheduled downtime, and the avoidance of environmental remediation expenditure that typically substantially exceeds the immediate repair bill following a significant spill or leak event. The magnitude of these savings establishes a compelling business case for adoption even in the absence of regulatory mandates.

#### 4.6 Impact on Key Operational Cost Drivers

Table 4 disaggregates the operational cost impact of predictive maintenance into its principal constituent elements, providing a more granular view of where the hybrid framework delivers the greatest financial benefit.

**Table 4** Impact of Predictive Maintenance on Key Operational Cost Drivers

Maintenance Approach	Annual Maintenance Cost (N)	Avg. Downtime (Days/Year)	Repair/Replacement Cost (N)	Operational Cost Savings
Traditional Reactive Maintenance	1.5 billion	30	600 million	N/A
Predictive Maintenance (Hybrid Model)	950 million	12	300 million	~35%

*Note.* Annual Maintenance Cost and Repair/Replacement Cost are expressed in Nigerian Naira (N). Average Downtime refers to the mean unscheduled downtime days per year attributable to pipeline failures. Operational Cost Savings represents the percentage reduction relative to traditional maintenance expenditure. Figures are indicative estimates based on sector-level cost data (Ekeu-wei and Ekeu-wei, 2024; Hector and Panjanathan, 2024).

As indicated in Table 4, predictive maintenance reduces average annual maintenance expenditure from N1.5 billion to N950 million—a reduction of approximately 37%—whilst cutting mean unscheduled downtime from 30 to 12 days per year, a 60% improvement in pipeline availability. Repair and replacement costs are halved, from N600 million to N300 million, reflecting the avoidance of catastrophic failure events that necessitate costly full segment replacements. The overall operational

cost saving of approximately 35% is consistent with findings reported by Hector and Panjanathan (2024) for predictive maintenance deployments in safety-critical industrial sectors.

## 5.0 DISCUSSION

### 5.1 Economic Implications

The quantitative results in Section 4 make a compelling economic case for adopting predictive maintenance in Nigeria's pipeline sector. The hybrid model's superior regression performance ( $R^2 = 0.96$ , RMSE = 8.3 days) relative to the traditional Weibull model ( $R^2 = 0.82$ , RMSE = 21.6 days) translates directly into more reliable maintenance scheduling: operators can plan and procure resources in advance of predicted failures rather than respond reactively. This reduction in scheduling uncertainty is the primary driver of the 35% operational cost saving shown in Table 4. The reduction in average downtime from 30 to 12 days per year is particularly

significant in the Nigerian context, where pipeline shutdowns frequently cascade into production losses, contractual penalties, and reputational damage to international off-takers (Ekeu-wei and Ekeu-wei, 2024; van Dinter *et al.*, 2024). Taken together, the economic evidence strongly supports the conclusion that hybrid predictive maintenance offers a financially sound investment for operators and a cost-reduction strategy of national significance.

### 5.2 Environmental Implications

The environmental dimension of predictive maintenance adoption is no less significant than the economic one. Nigeria's pipeline failures have for decades been associated with oil spills and gas leaks that have devastated agricultural land, contaminated water sources, and disrupted livelihoods in the Niger Delta (Amadhe *et al.*, 2024; Soomro *et al.*, 2022). The projected 40% reduction in oil spill incidents and 35% reduction in gas leaks shown in Figure 2 represent substantial environmental dividends achievable without major capital investment in new infrastructure. By identifying failure-prone segments before rupture, the hybrid framework enables operators to conduct targeted repairs during planned maintenance windows, replacing the reactive cycle of spill–contamination–remediation with a proactive cycle of detection–intervention–prevention. These environmental gains align with Nigeria's obligations under the NUPRC Methane Emissions Regulations (NUPRC, 2023) and reduce operators' regulatory liability exposure, reinforcing the economic case for adoption (Hussain *et al.*, 2023).

### 5.3 Policy Implications

The policy implications of the hybrid framework extend across three regulatory domains. With respect to maintenance regulation, the model's ability to generate legally defensible, distribution-free RUL prediction

intervals through conformal prediction (Equation 16) provides the technical basis for regulators to mandate predictive maintenance in pipeline integrity management. With respect to safety standards, the risk-tiered decision framework illustrated in Figure 1 can be formalised into regulatory inspection frequency requirements calibrated to model-derived risk scores rather than arbitrary fixed time intervals, producing a more rational and resource-efficient inspection regime. With respect to environmental protection, the quantitative relationship between predictive maintenance adoption and incident reduction demonstrated in Figure 2 supplies the evidential foundation for tighter environmental performance targets under the Petroleum Industry Act (Federal Republic of Nigeria, 2021) and associated NUPRC regulations. The convergence of economic, safety, and environmental evidence presented in Sections 4 and 5 confirms that the hybrid framework can serve as the technical cornerstone of a comprehensively reformed pipeline regulatory architecture.

## 6.0 POLICY RECOMMENDATIONS

### 6.1 Predictive Maintenance Regulation

To enhance the reliability and safety of Nigeria's pipeline network, the NUPRC and NMDPRA should mandate the use of certified hybrid predictive maintenance models for pipeline integrity management, particularly in high-risk and environmentally sensitive areas. Standardised protocols for pipeline monitoring, RUL model deployment, and failure prediction reporting should be developed to ensure consistency and comparability of compliance data across operators. The risk-based decision framework presented in Figure 1 provides a ready template for regulatory standardisation. Table 3 details a comprehensive set of policy actions recommended across nine regulatory domains.

**Table 5** Policy Recommendations for Predictive Maintenance Implementation in Nigeria's Pipeline Sector

Policy Area	Recommendation
Regulatory Guidelines	Mandate the use of certified hybrid predictive maintenance models for pipeline integrity management in all critical operational and environmentally sensitive areas.
Inspection Intervals	Replace fixed-interval inspection schedules with risk-proportionate schedules calibrated to model-derived RUL estimates and failure probabilities.
Data Monitoring	Require real-time pipeline monitoring using IoT sensors and SCADA systems; mandate submission of continuous monitoring data to NUPRC.
Maintenance Priority	Require operators to formally prioritise maintenance resources for segments with the lowest RUL predictions and highest failure probabilities.
Training and Certification	Establish accredited certification programmes for personnel responsible for deploying and interpreting predictive maintenance technologies.

Risk Assessment Framework	Develop a standardised, risk-based decision-making framework for pipeline integrity, underpinned by approved predictive model outputs.
Public Safety and Environmental Protection	Require that predictive maintenance programmes demonstrably reduce pipeline failure incidents, with measurable environmental and safety performance targets.
Incentives for Adoption	Introduce tax reliefs, accelerated depreciation, and capital allowances for qualifying expenditure on predictive maintenance systems and pipeline monitoring infrastructure.
Reporting and Compliance	Mandate periodic regulatory reporting of RUL model outputs, maintenance actions, and environmental performance outcomes by all licensed pipeline operators.

*Note.* Recommendations are derived from the quantitative findings in Sections 4 and 5, the regulatory frameworks of the Petroleum Industry Act (Federal Republic of Nigeria, 2021) and NUPRC Regulations (NUPRC, 2023, 2024), and best-practice evidence from the predictive maintenance literature (Amadheet *al.*, 2024; Hector and Panjanathan, 2024; van Dinter *et al.*, 2024).

Table 5 presents nine regulatory action areas spanning mandatory compliance, inspection scheduling reform, real-time data infrastructure, maintenance prioritisation, personnel certification, standardised risk assessment, environmental performance obligations, financial incentive structures, and regulatory reporting. These areas are not independent: progress on data monitoring (row 3) enables the risk-proportionate inspection scheduling advocated in row 2; the certification programme in row 5 ensures that personnel can correctly interpret the model outputs that underpin the risk assessment framework in row 6; and the reporting requirements in row 9 provide the compliance evidence needed to operationalise the incentive structures in row 8. The comprehensiveness of the table reflects the systemic nature of the transition from reactive to predictive maintenance, which demands coordinated reform across technical, regulatory, institutional, and human-resource dimensions.

### 6.2 Economic Incentives for Early Adoption

The Federal Government and the NUPRC should consider a phased incentive package to accelerate industry uptake. This could include accelerated depreciation for expenditure on pipeline monitoring equipment and predictive analytics systems; tax credits linked to demonstrated reductions in unscheduled downtime and pipeline failure frequency; and grant funding for capacity-building in data science and predictive maintenance engineering within Nigerian universities and technical institutions. Such measures would reduce the upfront financial barrier to adoption, particularly for smaller independent operators, and create competitive pressure on larger international companies to maintain their compliance standing. The cost-benefit

evidence in Tables 2 and 4 indicates that the fiscal exposure from such incentives would be more than offset by reduced environmental remediation costs, lower public health expenditure, and increased tax revenues from more reliable production.

### 6.3 Environmental Protection Measures

Predictive maintenance should be formally integrated into Nigeria's environmental compliance framework. The NUPRC should require operators to demonstrate, as part of their annual compliance submissions, that their pipeline integrity management programmes incorporate RUL-based predictive analysis meeting prescribed accuracy standards. Environmental performance targets expressed as maximum tolerable spill incident frequencies and failure rates should be established, with the hybrid model's projected impact values (Figure 2) providing an evidence-based baseline. Formal collaboration between pipeline operators and environmental agencies—including the National Environmental Standards and Regulations Enforcement Agency (NESREA)—should be institutionalised to ensure that model outputs inform both operational maintenance planning and environmental risk assessment under the NUPRC Methane Emissions Regulations (NUPRC, 2023).

### 7.0 CONCLUSION

This paper has demonstrated the technical capability and policy relevance of a hybrid neural–statistical framework for predictive maintenance in Nigeria's oil and gas pipeline sector. By integrating Feedforward ANN, LSTM, CNN, GNN, GAM, and EEW components into a stacked ensemble with conformal prediction intervals, the framework achieves an  $R^2$  of 0.96, RMSE of 8.3 days, MAE of 6.1 days, and a failure classification accuracy of 95.4%—performance levels that substantially exceed all standalone and traditional parametric benchmarks. These results translate into projected operational cost savings of approximately 35%, a reduction in unscheduled downtime from 30 to 12 days per year, a halving of repair and replacement expenditure, and significant reductions in environmentally damaging pipeline incidents.

The policy analysis confirms that the hybrid framework is well-suited to serve as the technical foundation of a reformed pipeline regulatory architecture under the Petroleum Industry Act (Federal Republic of Nigeria, 2021). The NUPRC and NMDPRA are positioned to translate the framework's outputs into enforceable maintenance standards, risk-proportionate inspection requirements, and measurable environmental compliance obligations. The nine-domain policy recommendations presented in Table 3 provide a structured pathway for this regulatory transformation. Realising the full potential of predictive maintenance in Nigeria's pipeline sector will require coordinated action across government, regulatory authorities, the oil and gas industry, and academia; however, the technical evidence presented in this paper confirms that the capabilities required are available, validated, and ready for deployment at scale.

### 8.0 FUTURE WORK

Future research should focus on three priority areas. First, integrating real-time data streams from deployed IoT sensor networks and SCADA systems into adaptive predictive maintenance systems that dynamically update RUL predictions as new operational data becomes available (Ezeja and Nwobi, 2024; Hussain *et al.*, 2024)—second, incorporating more advanced Bayesian uncertainty quantification techniques—including hierarchical Bayesian models and Bayesian deep learning—into the hybrid framework to improve prediction robustness in data-sparse or high-uncertainty environments, particularly for ageing pipeline segments with limited sensor coverage (Woldesellasse and Tesfamariam, 2025; Rayhana *et al.*, 2024). Third, extending the GNN component to multi-network pipeline topologies spanning different ownership boundaries and regulatory jurisdictions, addressing spatial risk propagation challenges that are especially acute in the interconnected infrastructure of the Niger Delta (Wang *et al.*, 2025; Wen *et al.*, 2024).

### ACKNOWLEDGMENT

The authors express gratitude to their supervisors, Prof. Umar Usman, Prof. Yakubu Musa, and Dr Abdulkarim Bello, for their invaluable guidance throughout this research. Special thanks are extended to the Petroleum Trust Development Fund (PTDF) for financial support, Usman Danfodiyo University Sokoto, and Federal University Gusau, for academic and professional opportunities, the Nigerian National Petroleum Corporation (NNPC), and the Department of Petroleum Resources (DPR), for providing the data utilised in this study.

### REFERENCES

Alobaidi, M. H., Meguid, M. A., and Zayed, T. (2022). Semi-supervised learning framework for oil and gas

- pipeline failure detection. *Scientific Reports*, 12(1), 13758. <https://doi.org/10.1038/s41598-022-17731-8>
- Amadhe, F. O., Anjorin, R. O., and Uwoghien, F. O. (2024). Advancements in machine learning for pipeline integrity management: A comprehensive review of predictive and optimisation techniques. *Cognisance Journal of Multidisciplinary Studies*, 4(11), 129-138.
- Brown, J., and Davis, S. (2024). Enhancing pipeline monitoring with Bayesian neural networks and uncertainty quantification: reliability. *Engineering and System Safety*, 214, 107911.
- Clark, N. J., Wells, K., and Lindberg, O. (2023). Dynamic generalised additive models (DGAMs) for forecasting discrete ecological time series. *Methods in Ecology and Evolution*, 14(3), 771-784. <https://doi.org/10.1111/2041-210X.13974>
- Cressie, N., and Wikle, C. K. (2021). *Spatial statistics: An introduction*. Wiley.
- Ekeu-wei, I. T., and Ekeu-wei, A. B. (2024). Economic losses from pipeline failures in Nigeria's oil and gas sector, 1990-2022: Trends, drivers, and implications for predictive maintenance policy. *Journal of Energy Policy and Regulation*, 6(2), 45-61.
- Ezeja, O. M., and Nwobi, C. G. (2024). A fuel pipeline monitoring and security system using wireless sensor networks (WSN). *Nigerian Journal of Technology*, 43(3). <https://doi.org/10.4314/njt.v43i3.14>
- Federal Republic of Nigeria. (2021). *Petroleum Industry Act, 2021*. Federal Government of Nigeria Official Gazette.
- Hector, I., and Panjanathan, R. (2024). Predictive maintenance in Industry 4.0: A survey of planning models and machine learning techniques. *PeerJ Computer Science*, 10, e2016. <https://doi.org/10.7717/peerj-cs.2016>
- Hussain, M., Zhang, T., and Seema, M. (2023). Adoption of big data analytics for energy pipeline condition assessment. *International Journal of Pressure Vessels and Piping*, 205, 105061. <https://doi.org/10.1016/j.ijpvp.2023.105061>
- Hussain, M., Zhang, T., Chaudhry, M. S., and Habib, M. (2024). Review of prediction of stress corrosion cracking in gas pipelines using machine learning. *Machines*, 12(1), 42. <https://doi.org/10.3390/machines12010042>
- Kumar, P., Gupta, M., and Kumar, S. (2022). Pipeline failure prediction models using survival analysis: A comparative study. *Journal of Infrastructure Engineering*, 18(1), 75-89.
- Nigerian Upstream Petroleum Regulatory Commission (NUPRC). (2023). *Gas flaring, venting and methane emissions (prevention of waste and pollution) regulations, 2023*—Federal Republic of Nigeria.
- Nigerian Upstream Petroleum Regulatory Commission (NUPRC). (2024). *2024 Annual report*. NUPRC. <https://www.nuprc.gov.ng>
- Rayhana, R., Xia, G., and Liu, Z. (2024). Towards next-generation NDE: Predictive analysis of pipeline integrity using machine learning. In *NDE 4.0, predictive maintenance, communication, and energy systems: The digital transformation of NDE II*. SPIE. <https://doi.org/10.1117/12.3009014>
- Shaik, N. B., Pedapati, S. R., Taqvi, S. A. A., Othman, A. R., and Dzibir, F. A. A. (2022). Recurrent neural network-

- based model for estimating the life condition of a dry gas pipeline. *Process Safety and Environmental Protection*, 164, 639–650. <https://doi.org/10.1016/j.psep.2022.06.047>
- Soomro, A. A., Mokhtar, A. A., Kurnia, J. C., Lashari, N., Lu, H., and Mubarak, H. (2022). Integrity assessment of corroded oil and gas pipelines using machine learning: A systematic review. *Engineering Failure Analysis*, 131, 105810. <https://doi.org/10.1016/j.engfailanal.2021.105810>
- Spandonidis, C., Giordamli, C., Dafnis, N., Giannopoulos, F., Michail, K., and Dimoulas, C. (2022). Evaluation of deep learning approaches for oil and gas pipeline leak detection using wireless sensor networks. *Engineering Applications of Artificial Intelligence*, 113, 104890. <https://doi.org/10.1016/j.engappai.2022.104890>
- van Dinter, R., Tekinerdogan, B., and Catal, C. (2024). Systematic review of predictive maintenance and digital twin technologies: Challenges, opportunities, and best practices. *PeerJ Computer Science*, 10, e1943. <https://doi.org/10.7717/peerj-cs.1943>
- Wang, Y., Chen, Z., Li, Y., Wu, J., Xie, W., and Chen, J. (2025). A survey on graph neural networks for remaining useful life prediction: Methodologies, evaluation and future trends. *Mechanical Systems and Signal Processing*, 224, 112154. <https://doi.org/10.1016/j.ymsp.2025.112154>
- Wen, Z., Jin, H., and Hua, Y. (2024). Temporal and heterogeneous graph neural network for remaining useful life prediction. arXiv preprint arXiv:2405.04336. <https://arxiv.org/abs/2405.04336>
- Wilson, J., Brown, J., and Davis, S. (2024). Conformal prediction for hybrid neural-statistical pipeline models. *Journal of the American Statistical Association*, 119(535), 1725-1740.
- Woldesellasse, H., and Tesfamariam, S. (2025). Risk assessment of gas pipeline using an integrated Bayesian belief network and GIS: Using Bayesian neural networks for external pitting corrosion modelling. *Canadian Journal of Chemical Engineering*, 103(1), 98–109. <https://doi.org/10.1002/cjce.25455>
- Wood, S. N. (2020). Inference and computation with generalised additive models and their extensions. *TEST*, 29(2), 307-339. <https://doi.org/10.1007/s11749-020-00711-5>